

PCIe Bus Four Port Card

Support Two RS232 and Two Ground Isolated

RS422/RS485 selectable



- ★Each port can set to RS422/RS485
- ★Easy to set by DIP Switch
- ★ Support ADDC feature in RS485
- ★ Suitable for industrial control
- ★ Suitable for Windows 2000/XP
- ★ Suitable for Vista & WIN7/8/10
- ★Suitable for Linux

A124I Specification :	
Serial Communication Controller :	Port capability :
*type : ASIX MCS9904.	*number of port : 4 ports per card.
	*Interface : RS232 in Port A & B.
<u>Hardware compatibility :</u>	Ground Isolated RS422/RS485
*PCIe bus slot.	in Port C & D.
	Note: Each port can set to RS422/RS485 by DIP
Software compatibility :	Switch.
* Windows 2000/XP.	*Baud Rate: each port can be configured to
* Windows Vista.	50921600bps. (RS232 to
* WIN7/8/10.	230400bps)
* Linux.	*Connector type: DB37 female connector.
* Other operation system.	*P485 cable support DB37 male to four DB9 male connector.
System I/O & IRQ mapping :	*A400 cable support DB37 male to four
* I/O mapping assigned by PCI BIOS.	DB25 male connector.
* Memory mapping assigned by PCI	Dimension :
BIOS.	*A124I card: 120 * 105 mm.
* four IRQ mapping assigned by PCI	*A124I model with standard PCIe bracket
BIOS.	<u>Environment :</u>
	*operating temperature $:0^\circ\!\mathbb{C}$ to $55^\circ\!\mathbb{C}$
	*operating humidity : 10% to 95% RH
	*storage temperature : $0^\circ C$ to $65^\circ C$
	*storage humidity : 5% to 95% RH

Performance upgrade capability and relative products :

*A102 : PCIe card support two Ground isolated RS232 ports.

*A132 : PCIe card support two RS422/RS485 ports.

*A112 : PCIe card support two RS232/RS422/RS485 ports.

*A104 : PCIe card support four RS232 ports.

*A134 : PCIe card support four RS422/RS485 ports.

*A168 : PCIe card support eight RS232 ports.

*A134I: PCIe card support four Ground isolated RS422/RS485 ports.

*A114: PCIe card support four RS232/RS422/RS485 ports.

***All names are the trademarks of their respective organization.

RAYON TECHNOLOGY CO., LTD.

