

OPe952 PCI Express Card

PCIe Bus Two Port Card



- ★ Suitable for **industrial control**
- ★ Suitable for **Windows 2000/XP/2003**
- ★ Suitable for **Windows Vista/WIN7/WIN8**
- ★ Suitable for **Linux**

OPe952 Specification :

Serial Communication Controller :

*type : Oxford 16950 compatible.

Hardware compatibility :

*PCIe bus slot.

Software compatibility :

- * Windows 2000/XP/2003.
- * Windows Vista/WIN7/WIN8.
- * Linux.
- * Other operation system.

Dimension :

- *OPe952 card: 80 * 70 mm.
- *OPe952 model with standard PCIe bracket.
- *OPe952L model with low profile PCIe bracket.

System I/O & IRQ mapping :

- *Memory mapping assigned by PCI BIOS.
- *one IRQ mapping assigned by PCI BIOS.

Port capability :

- *number of port : 2 ports per card.
- *Interface : RS232.
- *Baud Rate: each port can be configured to 50--115200bps.
- *Connector type: DB9 male connector.

Environment :

- *operating temperature : 0°C to 55°C
- *operating humidity : 10% to 95% RH
- *storage temperature : 0°C to 65°C
- *storage humidity : 5% to 95% RH

Performance upgrade capability and relative products :

- *A104 : PCIe card support four RS232 ports.
- *Epe358 : PCIe card support eight RS232 ports.
- *UTS040 box: USB to four ground isolated RS232 ports.
- *UTS004 box: USB to four ground isolated RS422/485 ports.
- *UTS485 box: USB to two RS232 and two ground isolated RS422/485 ports.
- *APORT040 box: IP to four ground isolated RS232 ports.
- *APORT202 box: IP to two RS232 and two ground isolated RS422/485 ports.

***All names are the trademarks of their respective organization.



RAYON TECHNOLOGY CO., LTD.

2F, No. 177, Chung Shan 2 Rd., Lu Chou, New Taipei city, Taiwan, R.O.C.
TEL: 886-2-82858362 FAX: 886-2-82857065
E-Mail: rayon@ms1.hinet.net ; info@rayontech.com.tw
WEB: <http://www.rayontech.com.tw>