

## **PCIe Bus Four Port Card**



★Suitable for industrial control
★Suitable for Windows 2000/XP/2003
★Suitable for Windows Vista/WIN7/WIN8
★Suitable for Linux

## **OPe954** Specification :

Sovial Communication Controllor:	System I/O & IBO manning :
<u>Serial Communication Controller :</u>	System I/O & IRQ mapping :
*type : Oxford 16950 compatible.	*Memory mapping assigned by PCI BIOS.
	*one IRQ mapping assigned by PCI BIOS.
Hardware compatibility :	
*PCIe bus slot.	Port capability :
	*number of port : 4 ports per card.
Software compatibility :	*Interface : RS232.
* Windows 2000/XP/2003.	*Baud Rate: each port can be configured to
* Windows Vista/WIN7/WIN8.	50115200bps.
* Linux.	*Connector type: DB44 female connector.
* Other operation system.	*R904 cable support DB44 male to four
	DB9 male connector.
Dimension :	
*OPe954 card: 93 * 70 mm.	<u>Environment :</u>
*OPe954 model with standard PCIe	*operating temperature : $0^{\circ}C$ to $55^{\circ}C$
bracket.	*operating humidity: 10% to 95% RH
*OPe954L model with low profile PCIe	*storage temperature : $0^{\circ}C$ to $65^{\circ}C$
bracket.	*storage humidity: 5% to 95% RH

## Performance upgrade capability and relative products 🔅

\*A102 : PCIe card support two RS232 ports.
\*Epe358 : PCIe card support eight RS232 ports.
\*UTS040 box: USB to four ground isolated RS232 ports.
\*UTS004 box: USB to four ground isolated RS422/485 ports.
\*UTS485 box: USB to two RS232 and two ground isolated RS422/485 ports.
\*APORT040 box: IP to four ground isolated RS232 ports.
\*APORT202 box: IP to two RS232 and two ground isolated RS422/485 ports.
\*APORT202 box: IP to two RS232 and two ground isolated RS422/485 ports.



## **RAYON TECHNOLOGY CO., LTD.**

2F, No. 177, Chung\_Shan 2 Rd., Lu\_Chou, New Taipei city, Taiwan,R.O.C. TEL: 886-2-82858362 FAX: 886-2-82857065 E-Mail: rayon@ms1.hinet.net ; info@rayontech.com.tw WEB: http://www.rayontech.com.tw