

MUX3927 IOPMUX CARD

☆ Intelligent Multiport Card ☆

- ☆ Statistical Multiplexer ☆
- ☆ 5V & 3.3V Universal PCI ☆
- ☆ Built-in 133MHz MIPS CPU ☆
- ☆ Built-in 16MByte buffer ☆
- ☆ Support upto 8 Boxes ☆
- ☆ Support upto 64 Ports ☆



- *Built-in 133MHz MIPS local processor. Faster and powerful for your system.
- *Support 3.3v & 5V PCI bus slot. Suitable for PC and server application.
- *Support UNIX & Linux system driver.
- ☆ One card can support upto 8 RMX828/RMX680E multiplexer box in any location. ☆
- *Support upto two cards and 128 ports per system.
- ☆ One card can replace one P960A card with eight A641 box and eight RMX680E statistical multiplexer. ☆

MUX3927 card Specification

System structure:

*MUX3927 card: 8 Composite port to 8 target RMX680E/RMX828 MUX.

*R801 cable: DB62M to 8 DB25M connector.

System memory:

*16MByte SDRAM

*1MByte Flash ROM.

System Processor:

*Type: 3927 MIPS CPU.

*Speed: 133MHz.

Hardware Compatibility:

*5V & 3.3V PCI bus slot.

Software compatibility :

*SCO Openserver UNIX.

*Linux system.

MUX3927 card Composite port capability:

*Port number: 8 (COM1--COM8)

*Interface: RS232/V.24.

*Connector type: DB25 male connector.

*Baud rate: ASYNC upto 230400bps.

Dimension :

*card: 15.7 * 11.0 (cm).

Environment :

*operating temperature : 5°C to 40°C

*storage temperature : 0°C to 65°C

*operating humidity : 10% to 90% RH

*storage humidity : 5% to 90% RH

Other Relative Products

*RMX680E multiplexer: support eight ASYNC channel port in one box.

*RMX828 multiplexer: support eight ASYNC channel port and two SYNC channel port in one box.

*GTS586 terminal server: support 16 serial port and one printer port.
support 10Base5, 10Base2, 10BaseT LAN connection.

***All names are the trademarks of their respective organization.



RAYON TECHNOLOGY CO., LTD.

2F, No. 177, Chung Shan 2 Rd., Lu Chou city, Taipei Hsien, Taiwan.

TEL: 886-2-82858362 FAX: 886-2-82857065

E-Mail: rayon@ms1.hinet.net

WEB: <http://www.computex.com.tw/rayon>

WEB: <http://www.rayontech.com>