

P232L PCI PORT Card

**One of the cheapest way to add
extra RS232 port in your worlds**



P232L Feature :

- ★ **Low Profile PCI Bus Two Port Card**
- ★ Suitable for **industrial control**
- ★ Suitable for **DOS** power user
- ★ Suitable for **Windows NT**
- ★ Suitable for **Windows 95/98/Me**
- ★ Suitable for **Windows 2000/XP/7/8/10**
- ★ Suitable for **Linux** system

P232L Specification :

Serial Communication Controller :

*type : 16C550 compatible with PGA support.

*speed : 22.1184MHz.

Hardware compatibility :

*5V PCI bus slot.

System I/O & IRQ mapping :

*one IRQ assigned by host.

*six 8Byte I/O mapping assigned by host

Software compatibility :

*MSDos

*Linux system

*Other operating system

*Windows NT system

*WIN 95/98/Me system

*WIN 2000/XP/Vista/WIN7/8/10 system

Port capability :

*number of port : 2 ports per card.

*Interface : RS232 compatible

*Baud Rate 50~115200bps

*Connector type : DB9 male connector.

Dimension :

*P232L card : **121 * 55 mm**

Environment :

*operating temperature : 0°C to 55°C

*operating humidity : 10% to 95% RH

*storage temperature : 0°C to 65°C

*storage humidity : 5% to 95% RH

Performance upgrade capability and relative products :

*P422N PCI PORT card: each card support two RS422/485 ports.

*UP422I PCI PORT card: each card support two isolated RS422/485 ports.

*UP485I PCI PORT card: each card support four isolated RS422/485 ports.

*RS4232-4 box: 4 RS232 to isolated RS232/422/485 convertor box.

*RS4232-8 box: 8 RS232 to isolated RS422/485 convertor box.

*TWIN485: Two Ground Isolated RS232 to RS422, RS485 Converter & Bridge.

***All names are the trademarks of their respective organization.



RAYON TECHNOLOGY CO., LTD.

2F, No. 177, Chung Shan 2 Rd., Lu Chou city, Taipei Hsien, Taiwan.

TEL: 886-2-82858362 FAX: 886-2-82857065

E-Mail: rayon@msl.hinet.net ; info@rayontech.com.tw

WEB: <http://www.computex.com.tw/rayon>

WEB: <http://www.rayontech.com.tw>