

P588U/P8485U

Universal PCI PORT Card

Flexible **3.3V & 5V PCI**

Powerful **RS232, RS422, RS485**



- ~~~~~
- I Support **eight RS422/485 port** in one card.
 - I Support any **RS232, RS422, RS485 port** combination in one card.
 - I Support **UNIX & LINUX** system driver.
 - I Support **Windows 95/98/Me/NT/2000/XP/2003** system driver.
 - I Support **DOS** driver.
 - I Support Auto-Data-Direction-Control (**ADDC**) feature in RS485 port.
 - I Support surge protector in **TXD/RXD** signal line.
- ~~~~~

P588U/P8485U Specification-----

System Structure

- ▲ intelligent PCIPORT Card.
- ▲ external cable with eight standard B25/DB9 connector (R801 cable or R804 cable).
- ▲ external cable to RS4232-8 box (option).

Serial Communication Controller

- ▲ type : 16550A compatible with PGA support.
- ▲ speed : 1.8432MHz. (can be used upto 7.3728MHz)

Hardware Compatibility

- ▲ 3.3V & 5V PCI bus slot.

Software Compatibility

- ▲ DOS Library
- ▲ WIN2000/XP/2003
- ▲ WIN95/98/Me
- ▲ Windows NT
- ▲ Linux
- ▲ SCO OpenServer

System I/O & IRQ mapping

- ▲ one 64byte and one 8byte I/O mapping assigned by PCI BIOS.
- ▲ one IRQ mapping assigned by PCI BIOS.

Port capability

- ▲ number of port : 8 ports per card.
- ▲ Interface :
 - RS232C * 8 (P588U card)
 - RS422/485 *8 (P8485U card)
 - RS232C *4 and RS422/485 * 4(P588U-4 card)

Note : we can accept user to order any combination in RS232 port and RS422/485 port with total eight ports in one card.

Note : each RS422/485 port can be set by DIP switch independently.

- ▲ Baud Rate :
 - each port can be configured to 50~115200bps.
- ▲ Connector type :
 - DB25 male connector. (with R801 cable)
 - DB9 male connector. (with R804 cable)

Dimension

- ▲ card : 141*106 mm.

Environment

- ▲ operating temperature : 0°C to 55°C .
- ▲ operating humidity : 10% to 95% RH.
- ▲ storage temperature : 0°C to 65°C .
- ▲ storage humidity : 5% to 95% RH.

Performance upgrade capability and relative products.

- ▲ user can connect with RS4232-8 box to support isolated RS422 or RS485 interface for each port independently.
- ▲ IOP3927 X-PORT card : support upto 64 ports per card.
- ▲ P1688U RAS-PRO Card : intelligent eight RS232 port card.
- ▲ P232 PCIPORT card : two RS232 port card.
- ▲ P422I PCIPORT card : two ground isolated RS422/485 port card.
- ▲ P485 PCIPORT card : four ground isolated RS422/485 port card.
- ▲ P584U PCIPORT card : universal four RS232 port card.
- ▲ P485U PCIPORT card : universal four RS422/485 port card.

I All names are the trade marks of their respective organization.



RAYON TECHNOLOGY CO., LTD.

2F, No. 177, Chung_Shan 2 Rd., Lu_Chou city, Taipei Hsien, Taiwan.

TEL: 886-2-82858362 FAX: 886-2-82857065

E-Mail: rayon@ms1.hinet.net

WEB: <http://www.computex.com.tw/rayon>

WEB: <http://www.rayontech.com>