# P8485US Universal PCIPORT Card

# Flexible 3.3V & 5V PCI Powerful RS422,RS485



- Support eight RS422/485 port in one card.
- Each port can be set to RS422 or RS485 independently.
- Support UNIX & LINUX system driver.
- Support Windows 95/98/NT/2000/XP/WIN7/10 system driver.
- Support DOS driver.
- Support Auto-Data-Direction-Control (ADDC) feature in RS485 port.

# **P8485US** Specification-

#### **System Structure**

▲intelligent PCIPORT Card.

▲ external cable with eight standard DB25/DB9 connector (R801 cable or R804 cable).

#### **Serial Communication Controller**

▲type: 16550A compatible with PGA support.

**▲**speed : 1.8432MHz.

#### **Hardware Compatibility**

▲3.3V & 5V PCI bus slot.

#### **Software Compatibility**

▲DOS Library

▲WIN2000/XP/2003/Vista/WIN7/8/10

**▲** WIN95/98/Me

▲Windows NT

**▲**Linux

▲SCO OpenServer

#### System I/O & IRQ mapping

▲one 64byte and one 8byte I/O mapping assigned by PCI BIOS.

▲one IRQ mapping assigned by PCI BIOS.

#### **Port capability**

▲number of port: 8 ports per card.

▲ Interface:

RS422/485 \*8.

Note: each RS422/485 port can be set by DIP switch independently.

▲ Baud Rate:

each port can be configured to 50~115200bps.

▲ Connector type:

DB25 male connector. (with R801 cable) DB9 male connector. (with R804 cable)

#### **Dimension**

**▲**card: 141 \* 106 mm.

#### **Environment**

 $\triangle$  operating temperature : 0°C to 55°C.

▲operating humidity: 10% to 95% RH.

 $\triangle$  storage temperature : 0°C to 65°C.

▲storage humidity: 5% to 95% RH.

# **Accessories**:

TB485: DB9 Female to RS485 terminal block kit.



## Performance upgrade capability and relative products.

▲ A138 card: PCIe support 8 RS422/RS485 ports per card.

▲ UP8485I Card: support 8 GROUND isolated RS422/RS485 port card.

▲ P588U PCIPORT card: universal eight RS232 port card.

▲ AP102 card: two RS232 port card.

▲ UP422I PCIPORT card: two ground isolated RS422/485 port card.

▲ UP485I PCIPORT card: four ground isolated RS422/485 port card.

▲ P584U PCIPORT card: universal four RS232 port card.

▲ P485U PCIPORT card: universal four RS422/485 port card.

• All names are the trade marks of their respective organization.



## RAYON TECHNOLOGY CO., LTD.

2F, No. 177, Chung Shan 2 Rd., Lu Chou, New Taipei city, Taiwan, R.O.C.

TEL: 886-2-82858362 FAX: 886-2-82857065

E-Mail: rayon@ms1.hinet.net; info@rayontech.com.tw

WEB: www.rayontech.com.tw