

S474io

serial port sharer



One RS485 Isolated master port Seven Isolated RS485 slave port Switching Power Built-in Less Expensive

- ◆ Support one isolated RS485 interface master port to seven Ground isolated RS485 interface slave port.
- ◆ Each port has ground isolation function to meet industrial environment.
- ◆ Support terminator resistor in RS485 interface port. Can use jumper to install or remove to meet impedance match rule.
- ◆ Built-in Switching power supply to accept 90 -- 260VAC or -48VDC input

S474io Interface Converter Specification

Input Port

*Connector type: DB25 Male

*Interface: RS485

this port is isolated with other port

Output Port

*Connector type: DB25 Male

*Interface: RS485

Each port is isolated with other port.

*RS485 signal Line: 422TXD+ and 422RXD+ short as DATA+ signal.

422TXD- and 422RXD- short as DATA- signal.

Note: RS485 interface with data direction auto control function.

Indicator Capability

*Power LED: green light for power on indication

TXD/RXD LED: double light for input port data transmission. each port has one LED indicator.

Dimensions

*S474io box: 29.8x13.5x5.5(cm)

Environment

*Operating Temperature: 5°C -- 40°C .

*Operating Humidity: 10% -- 90% RH.

*Storage Temperature: 0°C -- 65°C .

*Storage Humidity: 5% -- 90% RH.

Power Requirement

*AC input: 90 to 260 VAC

*DC input: -40 to -56 VDC

*Power consumption: 10W

Other Relative Products:

▲RS422HUB8 Interface Converter: one RS232 interface master port to eight ground isolated RS422 interface slave port.

©ALL name are the trademarks of their respective organization.



RAYON TECHNOLOGY CO., LTD.

2F, No. 177, Chung Shan 2 Rd., Lu Chou city, Taipei Hsien, Taiwan.

TEL: 886-2-82858362 FAX: 886-2-82857065

E-Mail: rayon@msl.hinet.net

WEB: <http://www.rayontech.com>