

SMK525_{ver2.0}

1U, Single Rail 17", 19" Rack LCD Console PS2 KB/MS



Specifications

Model No	SMK525-17	SMK525-19
KVM Switch	Single Port, VGA D-Sub 15 pin, PS/2 keyboard Mouse	
Drawer Design	1U, Single rail self-locking device	
Weight	12 kgs	
Dimension	442.4 x 44 x 480 mm (W x H x D)	
Power Supply	Built-in 60W, 100~240VAC Auto Switch, Operating Temp.: -20~70°C	
Construction	Heavy-duty steel	
Keyboard	104-key laptop type keyboard with touchpad, Option KB: CH, FR, GR, KR, RU, SP, UK, US Operating life of keys: 8 million cycles	
Physical Security	Key locking Mechanism	
Protection	Tempered glass protect LCD screen	
Power Consumption	3 watts stand-by, 25 watts in-use	
Operating Temp.	0 ~ 50°C (32 ~ 122°F)	
Storage Temp.	-20 ~ 60°C (-4 ~ 140°F)	
Humidity	0 ~ 90% RH	
Approvals	CE, FCC class A, RoHS	
LCD Display		
Size	17"	19"
Resolution	1280 x 1024	1280 x 1024
Brightness	300 cd/m2	300 cd/m2
Contrast Ratio	800 : 1	800 : 1
Viewing angle	160(H)/160(V)	170(H)/160(V)
Display Colors	16.7M	
MTBF	50,000 hours	

Features

- Meets EIA310c & IEC-3 specifications
- 1U, Single rail, built-in A-grade 17" or 19" TFT LCD Monitor, PS2 keyboard and touchpad
- PS2 interface for connecting to PC ports
- Key-locking mechanism to prevent unauthorized access
- 104 keys notebook type keyboard with touch pad
- Up to 130-degree monitor rotation for viewing flexibility
- Built-in rail self-locking device
- Tempered glass protect LCD screen



Packing List

1 *SMK Rack LCD KVM Console
1 * Power Cord
1 * 1.8m KVM cable
2 * Bracket
2 * Keys
1 * User's manual
1 * Screw Pack
1 * Foam with Box

Ordering Information

Product No.	Description
SMK525-17	Single Rail, 17" LCD, PS2 KB/MS, 1.8m KVM cable
SMK525-19	Single Rail, 19" LCD, PS2 KB/MS, 1.8m KVM cable
Option	
Keyboard layout: CH, FR, GR, KR, RU, SP, UK, US	