

# SMK595<sup>ver2.0</sup> 1U, Single Rail 17", 19" Rack LCD Console with 16 port PS2 KVM Switch



## Specifications

Model No	SMK595-17	SMK595-19
KVM Switch	16 port PS2 KVM switch	
Drawer Design	1U, Single rail self-locking device	
Weight	13 kgs	
Dimension	442.4 x 44 x 590 mm (W x H x D)	
Power Supply	Built-in 60W, 100~240VAC Auto Switch, Operating Temp.: -20~70°C	
Construction	Heavy-duty steel	
Keyboard	104-key laptop type keyboard with touchpad, Option KB: CH, FR, GR, KR, RU, SP, UK, US Operating life of keys: 8 million cycles	
Physical Security	Key locking Mechanism	
Protection	Tempered glass protect LCD screen	
Power Consumption	3 watts stand-by, 25 watts in-use	
Operating Temp.	0 ~ 50°C ( 32 ~ 122°F)	
Storage Temp.	-20 ~ 60°C ( -4 ~ 140°F)	
Humidity	0 ~ 90% RH	
Approvals	CE, FCC class A, RoHS	
LCD Display		
Size	17"	19"
Resolution	1280 x 1024	1280 x 1024
Brightness	300 cd/m2	300 cd/m2
Contrast Ratio	800 : 1	800 : 1
Viewing angle	160(H)/160(V)	170(H)/160(V)
Display Colors	16.7M	
MTBF	50,000 hours	



## Features

- Meets EIA310c & IEC-3 specifications
- 1U, Single rail, built-in A-grade 17" or 19" TFT LCD Monitor with 16-port PS2 KVM switch
- Key-locking mechanism to prevent unauthorized access
- 104 keys notebook type keyboard with touch pad
- Up to 130-degree monitor rotation for viewing flexibility
- Built-in rail self-locking device
- Tempered glass protect LCD screen
- No software required- Easy PC selection via Front push buttons, Hot keys, On Screen Display

## Packing List

1 * SMK Rack LCD KVM Console
1 * Power Cord
16 * 1.8m KVM cable
2 * Bracket
2 * Keys
1 * User's manual
1 * Screw Pack
1 * Foam with Box

## Ordering Information

Product No.	Description
SMK595-17	Single Rail, 17" LCD, 16 ports PS2 KVM, 16 x 1.8m KVM cable
SMK595-19	Single Rail, 19" LCD, 16 ports PS2 KVM, 16 x 1.8m KVM cable
Option	
Keyboard layout: CH, FR, GR, KR, RU, SP, UK, US	