

UCON485DB-I

Support one **RS232** input to

RS422/485 output **Interface Converter**

Double barrier Isolated

Triple way isolation to break any Ground loop.



- ★ Support data transmission LED display for each port
- ★ Easy to set as full-duplex RS422 or half-duplex RS485 interface via DIP switch.
- ★ Input to output connector with **double barrier Isolation** feature.
- ★ Can be used as **RS232 to isolated RS422 interface converter**.
- ★ Can be used as **RS232 to isolated RS485 interface converter**.

UCON485DB-I specifications :

Serial1 interface :

- ◆ Connector type: DB9 male connector.
- ◆ Ground isolated RS232.

NOTE: Serial1 port is isolated signal ground with power adapter input.

Serial2 interface:

- ◆ Connector type: DB9 male connector.
- ◆ Ground isolated RS422/RS485.

NOTE: RS422 or RS485 interface type set by DIP switch.

NOTE: Serial2 port is isolated signal ground with power adapter input.

NOTE: each port with 5 signal pin TX+ , TX- , RX+ , RX- , isolated GND

NOTE: In RS485 interface type TX+ and RX+ short as Data+ signal , TX- and RX- short as Data- signal. User can use TB485 module to exchange DB9 connector to 3 pin terminal block connector.

Power input :

- ◆ UP110/UP220 5V power adapter.
- ◆ Current consumption: 300mA.

LED indicator :

- ◆ PWR: DC power input ON indicator.
- ◆ **Serial1**: Isolated RS232 input port1 TXD/RXD signal activity.
- ◆ **Serial2**: Isolated RS422/RS485 output port2 TXD/RXD signal activity.

Dimension :

- ◆ UCON485DB-I box:
92mm (W) * 118mm (L) * 27mm(H)

Environment :

- ◆ operating temperature: 0°C to 55°C
- ◆ operating humidity : 0% to 95% RH.
- ◆ storage temperature : 0°C to 65°C .
- ◆ storage humidity : 5% to 95% RH.


Application :

RS232 to GROUND isolated RS422 interface converter.

RS232 to GROUND isolated RS485 interface converter.

Accessories :

TB485 : DB9 Female to RS485 terminal block kit.



Performance upgrade capability and relative products.

- ▲ UCON422DB-I box : Triple way Ground isolated RS422/485 to RS422/485 repeater/Bridge.
- ▲ UCON485DB-I box : Triple way Ground isolated RS232 to RS422/RS485 Interface converter.
- ▲ U2485DB-I box : Triple way Ground isolated Universal RS232 and RS422/RS485 input to RS232 and RS422/RS485 output Interface converter.

©All names are the trademarks of their respective organization.



RAYON TECHNOLOGY CO., LTD.

2F, No. 177, Chung-Shan 2 Rd., Lu-Chou, New Taipei city, Taiwan, R.O.C.

TEL: 886-2-82858362 FAX: 886-2-82857065

E-Mail: rayon@msl.hinet.net or info@rayontech.com.tw

WEB: <http://www.rayontech.com.tw>