

Support four ports in one box

Support four Ground isolated RS232 port

Powerful and Flexible for redundancy usage



★Support USB2.0 device controller
★512 Bytes FIFO for data transfer
★Support LED display for each port
★ four Ground Isolated RS232 for safety connection.
★ Support bus powered mode
★Use ASIX MCS7840 chip

UTS040 Specification :	
USB interface:	LED indicator:
*Connector type: USB B type connector.	*PWR: DC power input ON indicator.
*Device Controller: USB 2.0	*ATRD: RS232 port A TXD/RXD signal activity.
*stream FIFO size: 512Byte per serial port.	*BTRD: RS232 port B TXD/RXD signal activity.
	*CTRD: RS232 port C TXD/RXD signal activity.
RS232 interface:	*DTRD: RS232 port D TXD/RXD signal activity.
*Connector type: DB9 male connector.	
*Number of ports: 4 (port A, B, C, D)	<u>Power input:</u>
NOTE: port A,B,C,D have Isolated signal	*USB bus powered mode.
ground each other and USB bus.	*Current consumption: 400mA @ 5VDC.
	NOTE: user can use UTS040S in self-power
<u>Environment :</u>	mode to work with 5VDC power adapter.
*operating temperature: 0° C to 55° C.	
*operating humidity: 10% to 95% RH.	Accessories:
*storage temperature: 0° C to 65° C.	*U101 cable: 6 feet USB A type to B type
*storage humidity: 5% to 95% RH.	connector.
Dimension :	
*UTS040 box:	
90mm (W) * 150mm (L) * 27mm(H)	

Performance upgrade capability and relative products :

*TWIN485 box: two port ground isolated RS232 to RS422/485 converter.

*UTS400 box: USB to four RS232 ports.

*UTS114 box: USB to four RS232/RS422/RS485 settable ports.

*UTS004 box: USB to four ground isolated RS422/485 ports.

*UTS485 box: USB to two RS232 and two ground isolated RS422/485 ports.

***All names are the trademarks of their respective organization.



RAYON TECHNOLOGY CO., LTD.

2F, No. 177, Chung_Shan 2 Rd., Lu_Chou, New Taipei city, Taiwan,R.O.C. TEL: 886-2-82858362 FAX: 886-2-82857065 E-Mail: rayon@ms1.hinet.net or info@rayontech.com.tw WEB: http://www.rayontech.com.tw