## How to select RAYON's IP serial device server

1. General GPORT product line: just support RS232 interface

		<u> </u>			
Model	RS232	RS422/485	isolated RS232	isolated RS422/485	Total
GPORT104	4	x	×	×	4
GPORT108	8	X	×	×	8
GPORT116	16	x	×	×	16

2. Advanced APORT product line: support RS232, isolated RS232, isolated RS422/RS485 interface in serial port.

Model	RS232	RS422/485	isolated RS232	isolated RS422/485	Total
		13422/403		1801ateu K5422/485	
APORT100P	1	X	×	×	1
APORT111	1	X	X	1	1
APORT200	2	X	×	×	2
APORT101	1	X	×	1	2
APORT020	×	X	2	×	2
ILOG110	1	X	1	X	2
ILOG101	1	X	X	1	2
ILOG200	2	X	X	X	2
APORT201	×	X	×	1 + 1	2
APORT400	4	X	×	×	4
APORT040	×	X	4	×	4
APORT202	2	X	×	2	4
APORT022	×	X	2	2	4
APORT004	×	X	×	4	4
APORT800	8	X	×	×	8
APORT620	6	X	2	×	8
APORT602	6	X	×	2	8
APORT080	×	X	8	×	8
APORT008	×	X	×	8	8
APORT044	×	X	4	4	8

3. Intelligent IPORT product line: support RS232,RS422,RS485 interface in serial port via software setup or DIP switch to set interface type.

Model	RS232	RS422/485	isolated RS232	isolated RS422/485	Total
IPORT111	1	1	X	X	1
IPORT112	2	2	x	X	2
ILOG333	2	2	X	X	2
IPORT104P	4	x	X	X	4
IPORT108P	8	x	X	X	8
IPORT134	X	4	x	x	4
IPORT138	X	8	x	x	8
IPORT114	4	4	X	X	4
IPORT118	8	8	X	x	8
IPORT134i	x	X	х	4	4
IPORT138i	X	X	X	8	8